

## 1-Channel Gas monitoring system

### Properties

#### Measurement of gas concentrations

- ◆ Gas concentrations measured with NDIR sensors: CO, CO<sub>2</sub>, CH<sub>4</sub>, N<sub>2</sub>O
- ◆ Gas concentrations measured with electrochemical sensors: CO, NO, NO<sub>2</sub>, SO<sub>2</sub>, H<sub>2</sub>S.
- ◆ O<sub>2</sub> gemessen mit Partial pressure sensor
- ◆ Please ask for quote for other gases

#### Other measurements

- ◆ Atmospheric pressure
- ◆ Differential pressure
- ◆ Temperature using thermocouples
- ◆ Temperature using thermistors Pt-500

#### Processing and presentation of measured data

- ◆ Gas concentrations shown as ppm or mg/m<sup>3</sup>
- ◆ All results shown as instantaneous values on display
- ◆ Powerful PC programme for analyser settings and data communication
- ◆ Optional: Datalogger with 256 MB MMC (Memory card)
- ◆ Optional calculation of combustion parameters: Lambda, qA, Eta
- ◆ Optional calculation of NO<sub>x</sub> from NO or NO and NO<sub>2</sub>

#### Software capabilities

- ◆ Stationary operation: Zeroing and measurement times user programmable
- ◆ Permanent automatic check of the instrument
- ◆ Compensation of temperature drift of gas sensors

#### Hardware capabilities

- ◆ ABS housing for wall-mounting with internal ventilation
- ◆ Microprocessor controlled
- ◆ IR Sensors (CO, CO<sub>2</sub>, CH<sub>4</sub>, N<sub>2</sub>O) with short reaction time (T<sub>90</sub> < 15 seconds)
- ◆ Integrated Peltier sample conditioner with condensate pump and filter
- ◆ Solenoid valve for automatic ventilation during zeroing
- ◆ Membrane pump for sample extraction
- ◆ 4 current (0/4 - 20 mA) and 4 voltage (0 - 10 V). Freely allocated to the measurement channels
- ◆ Up to 3 LCD displays. Freely allocated to the measurement channels
- ◆ RS232C or RS485 connection for data transfer
- ◆ PC-Programm für komfortable und einfache Gerätekonfiguration und Datentransfer
- ◆ Optional integrated clock/calendar
- ◆ Optional: Converter for connection to USB or Ethernet

#### Possible uses

- ◆ Biogas plants
- ◆ Landfills
- ◆ Greenhouses
- ◆ Stationary control of combustion systems
- ◆ Incinerators
- ◆ Safety such as CO<sub>2</sub> (0...2000 ppm) or CH<sub>4</sub> (0...5 %)



**The maMoS-100 is a high quality stationary monitor for continuous measurement of one gas component. It is produced using all the newest technological developments. The monitor comes complete with filter, Peltier dryer and condensate pump.**

**It can be fitted with either infrared or electrochemical sensors or both. The possible sensors are: (electrochemical) O<sub>2</sub>, CO, NO, NO<sub>2</sub>, SO<sub>2</sub>, H<sub>2</sub>S or: (IR) CO, CO<sub>2</sub>, CH<sub>4</sub>, N<sub>2</sub>O.**

**The gas monitor is fitted with analogue outputs for current and voltage to allow control functions as well as measurement. There is also a digital data output if needed. The instrument operates fully automatically in one of two standard cycles:**

- ◆ continuous
- ◆ measurement according to set timetable

**Both cycles are freely programmable**

**madur**  
E L E C T R O N I C S

## Technical data

Component	Method	Range	Resolution	Detection Level	Accuracy	Time (T90)
<b>NDIR sensors</b>						
CO - Carbon monoxide-Volume concentration	IR Sensor	0...100 %	0.10 %	0.10 %	+/- 3 % rel., or 0.5 % abs.	45 s.
		0...50 %	0.10 %	0.10 %	+/- 3 % rel., or 0.3 % abs.	
CO <sub>2</sub> - Carbon dioxide-Volume concentration		0...25 %	0.01 % (100 ppm)	0.01 % (100 ppm)	+/- 3 % rel., or 0.15 % abs.	
		0...10 %	0.01 % (100 ppm)	0.01 % (100 ppm)	+/- 3 % rel., or 0.05 % abs.	
CH <sub>4</sub> - Methane-Volume concentration		0...5 %	0.01 % (100 ppm)	0.01 % (100 ppm)	+/- 3 % rel., or 0.03 % abs.	
		0...2.5 %	0.001 % (10 ppm)	0.001 % (10 ppm)	+/- 3 % rel., or 0.015 % abs.	
N <sub>2</sub> O - Nitrous oxide -Volume concentration	0...500 ppm	1 ppm	1 ppm	+/- 3 % rel., or 5 ppm abs.		
<b>Electrochemical sensors</b>						
CO - Carbon monoxide, Volume concentration	Electrochemical sensors	0...20000 ppm	1 ppm	1 ppm	+/- 5 % rel., or 5 ppm abs.	45 s.
NO / NO <sub>x</sub> - Nitric oxide, Volume concentration		0...5000 ppm	1 ppm	1 ppm		
NO <sub>2</sub> - Nitrogen dioxide, Volume concentration		0...1000 ppm	1 ppm	1 ppm		
SO <sub>2</sub> - Sulphur dioxide, Volume concentration		0...5000 ppm	1 ppm	1 ppm		
H <sub>2</sub> S - Hydrogen sulphide, Volume concentration		0...1000 ppm	1 ppm	1 ppm		
H <sub>2</sub> - Hydrogen, Volume concentration		0...2000 ppm	1 ppm	1 ppm		
<b>Partial pressure sensor</b>						
O <sub>2</sub> - Oxygen, Volume concentration	partial pressure sensor	0...25 %	0.01 %	0.01 %	+/- 5 % rel., or 0.2 % abs.	45 s.

### Operating data

Parameter	Description
Size	W x L x H: 380 x 300 x 140 mm
Weight without probe	ca. 4 kg
Supply	24 VAC / 120 W
Gas pump	Membrane pump 1.5 l/min
Display	LCD, for 1 measurement result
Data logger	MMC Card 256 MB
Analoge Ausgänge	Current 0/4 - 20 mA, Voltage 0 - 10 V, linear for each gas channel
Interface	RS 232C
Operating temperature	0°C ÷ 50°C
Storage temperature	-20 ÷ +55°C
Ambient humidity	5 ÷ 90 %, non-condensing

### Only NDIR sensors

Parameter	Description
Measuring method	NDIR light absorption, 1 channel with light modulation
Averaging time	2 ÷ 60 s freely programmable
Calibration	10 point calibration, stored in EEPROM. Correction of the calibration curve possible with zeroing and one calibration gas.
Recalibration	not usually necessary. If desired, a 2 point calibration can be carried out by the user.

### Only electrochemical sensors

Parameter	Description
Measuring method	electrochemical
Averaging time	2 ÷ 30 s freely programmable
Calibration	2 point calibration, variable
Recalibration	At least every 12 months